

SEALING KIT FOR SOLENOID VALVES WITH LOW ABSORPTION ELECTRIC COILS

Sealing kits are composed of a membrane, shutters and standard O-rings installed on our compressed air and vacuum 3-way valves and solenoid valves.
In presence of very hot fluids (up to 250 °C) or corrosive fluids, we can supply sealing kits in special compounds. Please contact our technical department.

Complete kit for solenoid valves:



07 01 13 and 07 02 13
07 03 13
07 03 13 LP
07 04 13 and 07 05 13
07 04 13 LP and 07 05 13 LP
07 06 13
07 06 13 LP

art. 00 07 271
art. 00 07 272
art. 00 07 290
art. 00 07 273
art. 00 07 291
art. 00 07 274
art. 00 07 292

Complete kit for solenoid valves:



07 01 53 and 07 02 53
07 03 53
07 03 53 LP
07 04 53 and 07 05 53
07 04 53 LP and 07 05 53 LP
07 06 53
07 06 53 LP

art. 00 07 275
art. 00 07 276
art. 00 07 293
art. 00 07 277
art. 00 07 294
art. 00 07 278
art. 00 07 295

Complete kit for solenoid valves:



07 03 43 and 07 04 43
07 03 63 and 07 04 63
07 05 43 and 07 05 63

art. 00 07 279
art. 00 07 279
art. 00 07 280

PILOT MEMBRANE FOR SOLENOID VALVES WITH LOW ABSORPTION ELECTRIC COILS



3D drawings available at www.vuototecnica.net

Art.	Valves art.	Connections	Material	Colour	Dimensions mm
00 07 104	07 03 43 - 07 04 43 07 03 63 - 07 04 63	G1/2" - G3/4"	reinforced NBR	Black	Ø 65
00 07 105	07 05 43 - 07 05 63	G1"	reinforced NBR	Black	Ø 76
00 07 229	07 01 13 - 07 01 53 07 02 13 - 07 02 53	G1/4" - G3/8"	Vulkollan®	Beige	49 x 35
00 07 230	07 03 13 - 07 03 53	G1/2"	Urepan® 65	Grey - orange	62 x 39
00 07 296	07 03 13 LP - 07 03 53 LP	G1/2"	Vulkollan®	Beige	62 x 39
00 07 231	07 04 13 - 07 04 53 07 05 13 - 07 05 53	G3/4" - G1"	Urepan® 65	Grey - orange	79 x 49
00 07 297	07 04 13 LP - 07 04 53 LP 07 05 13 LP - 07 05 53 LP	G3/4" - G1	Vulkollan®	Beige	79 x 49
00 07 232	07 06 13 - 07 06 53	G1" 1/2	Urepan® 65	Grey - orange	129 x 89
00 07 298	07 06 13 LP - 07 06 53 LP	G1" 1/2	Vulkollan®	Beige	129 x 89